

Outline:

- AEC-Q200 compliant
- Magnetic shielded structure:excellent resistance to electro Magnetic interference (EMI)
- Low loss,high efficiency,wide application frequency

Features:

- Core material: Alloy powder
- Environmental:RoHS,Reach compliant ,Halogen free
- Weight:5.97g
- Moisture Sensitivity:Level (MSL) 1 (unlimited floor life at 5 ~ 40°C, RH≤ 70% relative humidity).
- Operating temperature range: -55°C ~ +155°C (including coil's self temperature rise)
- Storage temperature range: -55°C ~ +155°C

Application:

- Engine and transmission control units.
- Diesel injection drivers
- Noise suppression for motors:windshield wipers/power seats/Power Mirrors/heating and ventilation blower/ HID lighting


1 Electrical Characteristics

Part No.	Inductance (μH) $\times 1$ $\pm 20\%$	D.C.R. (m Ω)		Isat (A) $\times 2$ Typical	Irms (A) $\times 3$ Typical
		Typical	Max.		
VSAB1365-R47M	0.47	1.00	1.20	45.0	48.0
VSAB1365-1R0M	1.00	1.70	2.30	24.0	29.0
VSAB1365-1R5M	1.50	2.50	2.90	18.0	27.5
VSAB1365-1R8M	1.80	2.70	3.10	17.9	27.0
VSAB1365-2R2M	2.20	4.00	4.50	17.7	21.0
VSAB1365-3R3M	3.30	5.00	5.80	17.0	19.5
VSAB1365-4R7M	4.70	7.90	8.60	13.5	15.0
VSAB1365-5R6M	5.60	9.30	10.0	12.0	14.0
VSAB1365-6R8M	6.80	10.0	11.5	10.5	13.5
VSAB1365-8R2M	8.20	12.0	13.8	10.0	12.0
VSAB1365-100M	10.0	15.0	17.8	9.00	11.0
VSAB1365-150M	15.0	24.5	28.0	7.20	8.50
VSAB1365-220M	22.0	35.0	39.5	6.40	7.00
VSAB1365-330M	33.0	60.0	69.0	4.40	5.50
VSAB1365-470M	47.0	72.0	85.0	3.90	4.20
VSAB1365-560M	56.0	95.0	105	3.70	3.80
VSAB1365-680M	68.0	103	117	3.20	3.30
VSAB1365-820M	82.0	120	138	2.80	2.50
VSAB1365-101M	100	135	160	2.50	2.30


All data is tested on 25°C ambient temperature

1. Inductance measure condition at 100kHz, 1.0V
2. Isat: the actual value of DC current when the inductance decrease approximately 20% of its initial value
3. Irms: the actual value of DC current when the temperature rise is $\Delta T 40^\circ\text{C}$ ($T_a = 25^\circ\text{C}$)









2 Product Dimensions (mm)














3 How to order:











4 Saturation Current vs Temperature Rise Current Curve









5 L vs Frequency




VSAB1365-6R8M




VSAB1365-8R2M




VSAB1365-100M




VSAB1365-150M




VSAB1365-220M




VSAB1365-330M




VSAB1365-470M




VSAB1365-560M




VSAB1365-680M











VSAB1365-820M











VSAB1365-101M




6 Impedance vs Frequency







VSAB1365-680M



VSAB1365-820M




VSAB1365-101M




7 Packing Specification

7.1 Carrier Tape Dimensions (mm)



※ Packing is referred to the international standard IEC 60286-3.

7.2 Reel Dimensions (mm)



7.3 Carton Dimensions and Packing Quantity


■ Inner Carton : 340×340×95mm

■ Outer Carton : 360×360×370mm

Product Series	Quantity / Reel	Inner Carton Quantity	Outer Carton Quantity
VSAB1365	400pcs	(400×2) = 800pcs	(800×3) = 2400pcs

8 Soldering Specification

8.1 Reflow Profile for SMT Components



8.2 Classification of Peak Package Body Temperature (Tp)

	Package Thickness	Package Volume		
		<350 mm ³	350 ~ 2000 mm ³	>2000 mm ³
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6 ~ 2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

- 9.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 9.2 Product in packing storage condition:temperature 5 ~ 40°C, RH≤ 70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 9.5 Always handle products with care.
- 9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 9.7 When this product will be used on a similar or new project to the original one,
sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 9.11 Refrain from rinsing product. If necessary, please consult with us.
- *9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.