

Outline:

- High saturation current to storage higher energy, capable of carrying higher peak transient current.
- Inductance value and DC bias capability are less affected by temperature and have high stability.
- Compact structure, high power density, can be operated in high current applications continuously.
- Flat wire winding, low DC resistance, good heat dissipation performance and low temperature rise.
- Magnetic shielded structure reduces electromagnetic emissions and conducted interference, and improves electromagnetic compatibility (EMC).


Features:

- Core material: Composite.
- Environmental: RoHS compliant, halogen free.
- Weight: 51g.
- Moisture Sensitivity: Level (MSL) 1 (Unlimited floor life at <math><30^{\circ}\text{C}</math> / 85% relative humidity).
- Operating temperature range: . (Including coil's temperature rise).
- Storage temperature range: .

Application:


- PV inverter/Industrial control/New energy.
- DC /DC converters/Motherboards/Filter.
- High current switching regulators.

1 Product Dimensions (mm)



Inductance	1.9 μH -2.2 μH	2.8 μH -4.3 μH	5.1 μH -5.6 μH	6.5 μH -7.1 μH	8.0 μH -8.8 μH	10.0 μH
A(mm)	2.50	2.00	1.75	1.50	1.35	1.20
B(mm)	14.3	14.3	14.7	14.7	15.3	15.3
C(mm)	3.50	3.00	2.50	2.50	2.00	2.00

Reference Hole Pattern



※ Date code will be changed by manufacture date.


2 Electrical Characteristics

Part No.	Inductance (μH)※1 $\pm 20\%$	D.C.R. (m Ω)		Isat (A)※2 Typical	I _{rms} (A)※3 Typical
		Typical	Max.		
CPAS2222-1R9MC	1.90	0.62	0.80	76.0	57.0
CPAS2222-2R2MC	2.20	0.62	0.80	70.0	57.0
CPAS2222-2R8MC	2.80	0.74	0.85	64.0	49.0
CPAS2222-3R2MC	3.20	0.74	0.85	56.0	49.0
CPAS2222-3R9MC	3.90	0.77	0.90	50.0	47.0
CPAS2222-4R3MC	4.30	0.77	0.90	48.0	47.0
CPAS2222-5R1MC	5.10	1.10	1.40	44.0	42.0
CPAS2222-5R6MC	5.60	1.10	1.40	42.0	42.0
CPAS2222-6R5MC	6.50	1.47	1.80	42.0	37.0
CPAS2222-7R1MC	7.10	1.47	1.80	36.0	37.0
CPAS2222-8R0MC	8.00	1.70	2.00	38.0	34.0
CPAS2222-8R8MC	8.80	1.70	2.00	31.0	34.0
CPAS2222-100MC	10.0	2.08	2.50	35.0	32.0









All data is tested on 25°C ambient temperature






1. Inductance measure condition at 100kHz, 0.1V.
2. Isat: the actual value of DC current when the Inductance decrease 30% of its initial Value.
3. I_{rms}: The actual value of DC current when the Temperature rise is $\Delta T 50^{\circ}\text{C}$ ($T_a = 25^{\circ}\text{C}$)

3 How to Order




4 Saturation Current vs Temperature Rise Current Curve






5 Inductance vs Frequency Curve


CPAS2222-1R9MC




CPAS2222-2R2MC




CPAS2222-2R8MC




CPAS2222-3R2MC




CPAS2222-3R9MC




CPAS2222-4R3MC




CPAS2222-5R1MC




CPAS2222-5R6MC




CPAS2222-6R5MC




CPAS2222-7R1MC




CPAS2222-8R0MC











CPAS2222-8R8MC




CPAS2222-100MC




6 Impedance vs Frequency Curve




CPAS2222-6R5MC




CPAS2222-7R1MC




CPAS2222-8R0MC



CPAS2222-8R8MC




CPAS2222-100MC



7 Packing Specification


7.1 Plastic Tray Dimensions (mm)



Packaging Unit (Pcs)	Material
20	APET

L typ	W typ	H typ	No. of Tray (Pcs)	Packaging Unit(Pcs)	Material
265	205	34	1	20	Paper

7.2 Packing(mm)



L typ	W typ	H typ	No. of Inner Carton(Pcs)	Packaging Unit(Pcs)	Material
275	232	261	7	140	Paper

8 Notice of Use

- 8.1 Special reminder: circuit design, component placement, PCB size and thickness, cooling system, etc., all will affect the product temperature. Please verify the product temperature in the final application.
- 8.2 Product in packing storage condition: < 30°C , < 85%RH.
If taken out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminal (electrodes), affecting soldering status.
- 8.3 A storage of Codaca electronic products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 8.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust, or corrosion.
- 8.5 Always handle products with care.
- 8.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 8.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different conditions of usage.
- 8.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., in abnormal conditions protective devices or protection circuit in the end product.
- 8.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 8.10 If used in potting compound, the magnet wire coating might be damaged, please consult with us.
- 8.11 Refrain from rinsing product. If necessary, please consult with us.
- *8.12 Codaca electronic products without "V" prefix are qualified for industrial product requirements, and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields. Codaca electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronics or higher application fields related to safety when without being aware of it.